



The Tumbler Features:

- Concentrated drying means efficient use of energy and that equates to improved throughput.
- Stainless steel construction and extra-wide hinges make sure the door stands up to frequent opening and closing and the rough demands of a busy on-premises laundry environment.
- The self-cleaning lint screen and large lint compartment mean employees spend less time cleaning.
- Paint is applied to the outside and inside of the cabinet electrostatically for superior bonding and corrosion resistance.
- Cissell's self-adjusting all-belt drive system reduces maintenance and delivers quieter operation.

EXCEPTIONAL CHOICES

For more than half a century, Cissell has been an industry leader in the design and innovation of laundry equipment. The result of our building durable, reliable and affordable equipment has been *Exceptional Choices* for our customers. Cissell offers outstanding quality, reliability, technical support and dependable distributors.

Cissell's drying tumblers are recognized worldwide for producing superior results and maximum productivity. Your dryers always will give you fast drying while saving energy. Our high-performance laundry equipment is built to give you complete control to tailor each wash to the specific requirements of the individual load. In addition, these drying tumblers offer an excellent blend of speed and efficiency to keep your on-premises laundry running at its highest level of productivity. *Exceptional Choices* — it's what makes Cissell the best overall value for your laundry.

EXCEPTIONAL CONTROL

Cissell drying tumblers offer intuitive controls, so managers spend less time training new employees. Our tumblers are offered with either microprocessor or digital controls.

The **DMP Micro-Control** features five preset drying cycles, with additional programmability. It also has an anti-wrinkle safety tumble and an easy-to-read digital display.



Cissell's **Digital Control** enables operators to set drying time (0-60 minutes), cool-down time (0-15 minutes) and temperature. It also features one-touch cycle repeat, extended tumble and easy-to-read digital displays.

EXCEPTIONAL VALUE

For more peace of mind, all Cissell drying tumblers come with an exceptional three-year warranty. We will cover any non-perishable part that fails due to defect in material or workmanship for three years from the date of installation. No one else gives you so many advantages with so much affordability.

Specifications

	50 lb Tumbler	75 lb Tumbler
Width - in (mm)	38 5/8" (981)	38 5/8" (981)
Depth - in (mm)	47" (1194)	53" (1346)
Height - in (mm)	76 5/8" (1946)	76 5/8" (1946)
Cylinder Depth - in (mm)	30" (762)	36" (914)
Cylinder Diameter - in (mm)	37" (939)	37" (939)
Cylinder Volume - cu. ft. (liters)	18.6 (528)	22.4 (634)
Door Opening - in (mm)	26 7/8" (683)	26 7/8" (683)
Dry Capacity Filling - lb (kg)	50 (22.7)	75 (34)
Filling Ratios	20:1 = 26.4 kg	20:1 = 31.7 kg
Air Outlet Diameter - in (mm)	8" (203)	8" (203)
Airflow - cfm (liters/sec.)	60 Hz: 750 (354) 50 Hz: 750 (354)	60 Hz Gas and Steam Models: 920 (434) Electric and 50 Hz Gas and Steam Models: 750 (354)
Energy Data	Gas Models: 120,000 Btu/hr (35.1 kW) Steam Models: 5.1 BHP @ 100 psi (6.9 bar) 178,000 Btu/hr (52.0 kW) 3.4 BHP @ 15 psi (1.0 bar) 119,000 Btu/hr (34.8 kW) Electric Models: 30 kW	Gas Models: 165,000 Btu/hr (48.3 kW) Steam Models: 6.1 BHP @ 100 psi (6.9 bar) 210,000 Btu/hr (61.6 kW) 4.1 BHP @ 15 psi (1.0 bar) 141,000 /Btu/hr (41.2 kW) Electric Models: 30 kW
Electrical Specifications	Gas & Steam Models: Amps 120/60/1 9.3 200-208/240/60/1 5.1 200-208/240/60/3 2.8 380/60/3 1.6 460-480/60/3 1.4 230-240/50/1 6.3 200/50/3 3.3 230-240/50/3 3.1 380/400-415/50/3 1.6 Steam Only Models: 440/60/3 1.4 Electric Models: 30 kw 200-208/60/3 89 240/60/3 79 380/60/3 47 440/60/3 41 480/60/3 38 200/50/3 84 230/50/3 73 240/50/3 79 380/50/3 47 400-415/50/3 43 Electric Models: 21kW 240/50/1 93	Gas & Steam Models: Amps 120/60/1 13.8 200-208/240/60/1 7.6 200-208/240/60/3 3.8 380/60/3 1.8 460-480/60/3 1.9 230-240/50/1 6.7 200/50/3 3.5 230-240/50/3 3.5 380/400-415/50/3 1.8 Steam Only Models: 440/60/3 1.9 Electric Models: 30 kw 200-208/60/3 89 240/60/3 79 380/60/3 47 440/60/3 41 480/60/3 38 200/50/3 84 230/50/3 73 240/50/3 79 380/50/3 47 400-415/50/3 43
Plumbing Connections	Gas Models: 1/2" NPT Steam Models: 3/4" NPT	Gas Models: 1/2" NPT Steam Models: 3/4" NPT
Net Weight - lb (kg)	545 (247)	615 (279)
Shipping Weight - lb (kg)	602 (273)	677 (307)
Shipping Dimensions - in (mm)	W 33" (838)	35 1/2" (902)
	D 49" (1245)	54" (1372)
	H 69" (1753)	85" (2159)
Agency Approvals	Gas Models: CSA Star, CSA Flame, cCSA _{US} , CE, Electric & Steam Models: cCSA _{US} , CE	Gas Models: CSA Star, CSA Flame, cCSA _{US} , CE, Electric & Steam Models: cCSA _{US} , CE

Tumbler models are made to suit a variety of electrical service characteristics. See your Cissell distributor for specifications. Gas models are certified by CSA International. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumbler.

Due to continuous improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

Printed in the U.S.A.



Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber.



P.O. Box 990 • Ripon, WI • 54971-0990

888-223-2980

www.cissellmfg.com

